Circuit Breakers

IOHN TRAYNA



THE VIDEO REPOSITIONER: A New Tool for TV Producers

There has always been a drive to bring video closer to film in production technique and postproduction capabilities, Traditionally, the primary roadblock in video has come with "in the can" or prerecorded imagery. Although technology has long provided video with the capability of mixing prerecorded tapes and treating them as live sources, the composition of the prerecorded image has remained predominantly sacro sanct and unchangeable.

It was with the introduction of digital technology that innovators first began readjusting the composi-

John Trayna is teaching courses in video production and video art at New York University and Cooper Union.

tion of prerecorded images. Field/ frame-store and frame-compression devices represented the first such attempts. Even some of the new digital switchers allow unique combining of several nonsynchronous sources. In all cases, the prerecorded images are dealt with on a generally holistic level and it has been impossible to reconstruct the composition of elements within the frame of one or more prerecorded sources of video. In film, the problem has long been remedied by the optical printing process, leaving such goals in video to be accomplished by present tense or "real-time" production tech-

That is, until now! Rutt Electrophysics, manufacturers of the RuttEtra Synthesizer has recently made available the Video Repositioner. Selling for \$6,800, Rutt's Video Repositioner is a unique little "blackbox" device that is specifically designed for reconstructing the composition of live and/or prerecorded frames of video when dealing with more than one source. So far, it has evoked positive reaction from major production houses. EUE Screen Gems and one of the tv networks have already purchased the Repositioner while broadcast stations from around the country have begun placing

The Video Repositioner is small in size. Designed for easy rack-mounting, it is 19 inches wide and only 31/2 inches high by 15 inches deep. It functions in a similar manner to the standard pulse-cross monitor by horizontally and vertically repositioning incoming sync to be outputted to the downstream production chain. The device requires time-base corrected or processed video to work and will not accept helical or helical gen-loc quality video. Vertical repositioning is accomplished one line at a time and horizontal repositioning is at a rate of 1X subcarrier. It performs by stripping the original sync and re-inserts properly re-timed sync information.

PRODUCTS



Min. order: 1 carton of 12

UCA 10								3	12.08 ea	3
UCA 15										
UCA 20							,		14.67 ea	3
UCA30									16.58 ea	1
UCA 40									19.25 ea	3
UCA 50									21.95 ea	1
UCA 60									22.95 ea	9
UCS 20	(MINI)								15.25 ea	9

POSTPAID Calif. Residents add tax For other items or quantities Phone collect or direct

(213) 451-1604

919 Broadway P.O. Box 1077 Santa Monica, CA 90406



Go Projectapix with designer-award

cabinetry and electronics...proven to be the ultimate in super-screen tv. Write For Specification Sheets On: CEILING & FLOOR UNITS. **LENSES & SCREENS**

NEW YORK NY 10019 TELEPHONES: (212) 765-7869

Get more Info. Circle Reader Card No. 126



Idea-filled planner for training and education

Just published guide describes dozens of ways to get more use from your present video equipment and software. Wilson Video Consoles, VTR Centers, TV Mounts and mobile Tables provide flexibility and efficiency. Equipment ideas to fit every size budget. Write for free planning guide and full color brochure.



H. WILSON CORPORATION

The device accepts standard composite video and will provide horizontal and vertical drives, subcarrier, composite blanking, composite sync, burst flag, and reference video. There is both a bypass switch and an auto-bypass feature that takes effect whenever the repositioner is powered down.

The actual repositioning of video is accomplished through four buttons: north, south, east and west. There is a digital L.E.D. readout indicating how far out of center images have been moved. There is also an onboard memory so that the operator can instantly return to a preset position. Movements are accomplished by selecting the desired direction and pushing the appropriate button. Press once to move a single step or hold the button for continuous movement. The Repositioner can even create horizontal pans or traveling mat effects similar to those accomplished in film through the use of optical printers. The electronics are strictly "state of the art," Completely solid state, the unit employs TTL and C-MOS logic with discrete and IC processing or video. All pots and switches are hermetically sealed, thus eliminating static and noise problems resulting from "dirty pots." There is instantaneous warm-up as well as automatic switchover to bypass whenever power is lost.



"The finest and most complete libraries available."
"Urite for free catalogs"

Thomas J. Valentino, Inc.



Get more Info. Circle Reader Card No.144



Everything from cartoons to features, local for hour programs for as little as \$49.95. Write for our Free Video Catalog.

CINEMA CONCEPTS, INC. 914 Main St. Chester Ct. 06412, (203)526-9513

Main St. Chester, Ct. 06412 (203) 526-5 Dealer Inquiries Invited

Get more Info. Circle Reader Card No.107

It should be emphasized that whenever the Video Repositioner is used, it affects the entire frame of video. When images within a given picture are moved, the edges move into view. The operator may then key or insert the repositioned image into a background and mask the edges. It's also important to differentiate the Repositioner from field and frame storage devices because it will not store video. Movement is accomplished by altering the phase of the equipment being used to generate or playback the image. Moreover, the Video Repositioner represents as little as one-tenth the cost of such devices.

A good example of how the Repositioner may be used can be seen in a Ford Motor Company commercial recently shot at EUE Screen Gems in New York City. The commercial called for a long pull-back of the camera in order to provide a full wide side perspective of the automobile. In doing so, however, the producers found that the stage being used to shoot the commercial was not guite tall enough so that when the camera was pulled back, the top of the curtain was revealed. Rather than take the time and cost to completely restage the commercial,

producers simply performed a softwipe and repositioned a section of the curtain to re-insert it at the top of the screen in the shots in question.

Some observers of the video scene feel that the Repositioner will expand the horizons of libraries of already existing video footage. The Repositioner will allow the addition of new pictures or graphics onto the older images. This could make it an ideal piece of hardware in the industrial, educational and scientific markets.

The Video Repositioner is currently available from Educational Electronics, Hollywood, Cal.; Sound Systems, Inc., Long Island, N.Y., and directly from Rutt Electrophysics, New York City. There is a sixty-day waiting period for delivery. I have little doubt that this device can have a major effect on contemporary production hardware and techniques. As such, it deserves serious consideration by producers and engineers alike.

Comments, questions, and information about new hardware are welcome and should be addressed to John Trayna, Videography, 750 Third Ave., New York, N.Y. 10017.

34 INCH U-MATIC VIDEO CASSETTES

Brand New
Major Manufacturer
First Quality Tape
Fully Guaranteed

Fully Guaranteed
"BUY A CASE"

1575 KCA 60

1125 KCA 30

20 per case BULK

12 per case with storage album at small extra cost.

ALL LENGTHS IN STOCK

Private label packaging avail-

able at no extra cost!

ASSOCIATED MAGNETIC

PRODUCTS INC.
20001 McDonald Ave.

20001 McDonald Ave. Brooklyn, New York 11223 (212) 339-9084

Get more Info. Circle Reader Card No.104

TENTEL FOR TENSION NOW MORE THAN EVER



Shown measuring the critical supply tension on a Sony 2850

FLAGGING? SIGNAL DROP-OUTS? INTERCHANGEABILITY?

The TENTELOMETER tape tension gage can help isolate and correct these problems and others on your reel to reel and your U-matic machines by measuring dynamic tape tension. Priced from \$179.00 complete

Send for Your FREE 8 pg. TEN-TELOMETER instruction and application manual or call today:



urtner Avenue, Campbell, CA (408) 377-6588

See us at New York VIDEO EXPO, Booth 309

Cet more Info Circle Reader Card No 141

ore milo. Circle Reader Card 140, 141